GZF5200KM

5M Roll-To-Roll LED UV printer!




- Up to 28 Konica 1024i/ Konica 1024a high-speed print heads.
- Up to **5200 mm** of printing width
- Dual water cooling LED UV lamps are effective and energy saving.
- Negative pressure system assures stable ink supply and nozzle jetting.
- White ink stirring system prevents print head clogging & enables stable printing.
- 4 jumble pneumatic rubber rollers ensure steady and accurate media delivery.
- Optional separate feeding and taking up system is ideal for soft media such as PVC backlit film.
- AC servo system with speed reducer assures quiet, stable & accurate carriage movement.
- Water cooling printing platen offers wrinkle-free delivery for the temperature sensitive materials.

GONGZHENG


ITEM	SPECIFICATION			
Model	GZF5200KM			
Print Head	8~28 Konica 1024i/ Konica 1024a print heads			
Head Config.	2XCMYK; 2XCMYK+2XW 2XCMYKLcLm; 2XCMYKLcLm+2XW 4XCMYK			
Curing System	LED UV Curing System			
Ink	UV curable ink			
Colors	Standard: CMYKLcLm, Optional: W			
Ink Supply System	Negative pressure system + White ink stirring system.			
Cleaning System	Positive Purging System with solenoid valves			
Servo System	AC motor with speed reducer			
Media System	4 rubber rollers + separate feeding and taking up system (optional)			
Media Type	Backlit, Banner Flex, Canvas, Mesh Paper, Synthetic Paper, PVC, Reflective Film, Sticker, Tarpaulin, Textile, Vinyl, Wallcoverings.			
Media Width	Max. 5200mm			
Printing Width	Max. 5200mm			
Printing Speed	**Konica 1024a**	Resolution	2 groups heads	4 groups heads
	Draft Production Quality Mode Hi-Precision	480x1080dpi 480x1440dpi 480x2160dpi 480x2880dpi	102.3m²/h 78.2m²/h 54.4m²/h 41.4m²/h	178m²/h 142.5m²/h 102m²/h 80.8m²/h
	Konica 1024i	Resolution	2 groups heads	4 groups heads
	Draft Production Quality Mode Hi-Precision	540x1080dpi 540x1440dpi 540x2160dpi 540x2880dpi	105m²/h 80m²/h 55m²/h 41m²/h	186m²/h 145m²/h 103m²/h 79m²/h
Data Interface	USB3.0			
Working Environment	Temperature: 20℃~28℃, Humidity: 40%~70%			
Software	Onyx+GZ Print Manager			
Image Format	Bitmap, TIF, Quark Xpress, JPEG, EPS, PDF			
Power	Single-phase, 50/60Hz, AC220V±10%, 32A, Regulator: 10kVA			
Dimension (Installed/Packed)	8350x1615x2040mm/8650x1800x2470mm(Printer); 670x480x880mm/740x530x900mm(Water cooling unit)			
Weight(N.W./G.W.)	6400kgs/7555kgs(Printer); 70kgs/75kgs(Water cooling unit);			


**Specifications are liable to change without prior notice.*


Main Features



Konica 1024i/ 1024a print heads


Negative Pressure System


Rubber Roller Feeding System


Separate feeding& taking up system
(optional)


Water cooling platen


LED UV lamp & Anti-collision unit

Gongzheng Group Co., Ltd.

Add: Miaobei Village, Yongjia County, Wenzhou City, Zhejiang Province, China 325102
Tel: +86-577-67319778
Fax: +86-577-67319775
Email: gzsales@gongzheng.com
Web: www.gongzheng.com

Ver 2020.09.19

Authorized distributor: