


Polyart for HP Indigo

- Coating for HP Indigo on two sides
- Filled HDPE film
- Cavitated core (density = 0.8 g/cm³)
- Simultaneous biaxial orientation



Property	Method	Units	Typical values			
Weight	ISO 536	g/m ²	124	154	224	274
Thickness	DIN 53370	µm	170	200	287	340
Density		g/cm ³	0.73	0.77	0.78	0.80
Whiteness	ISO 2470	%	90	90	90	90
Opacity	DIN 53146	%	97	97	98	98
Tensile strength	ISO 527-3	N/mm ²				
	MD					
	TD	36	33	29	27	
Elongation @ break	ISO 527-3	%				
	MD					
	TD	115	120	135	200	
Tear strength	ASTM	N/mm				
	MD					
	TD	D1004-66	129	124	115	112

Advice in this document is based on practical field experience and given in good faith but Arjobex, the manufacturer of Polyart synthetic papers, may not be held liable for loss or damage arising from action based on this information.



Features and Benefits

- Certified on all HP Indigo digital sheet presses including the new 5600
- Resists wide temperature variations: -60°C to +60°C
- Water and tear resistant
- No static issue
- No grain direction
- Die-cuts extremely well
- Very good folding
- Available in sheets and also in reels for WS series 4000 & 6000

